MUSICAL FIDELITY



V90-LPS Phono Stage

High Performance Phono

The V90-LPS is a modestly priced, very high performance MM/MC phono stage with superb technical performance.

In our opinion, there are five critical areas where a phono stage must achieve excellence:

- 1. RIAA correction
- 2. Correction above 20 kHz
- 3. Low distortion
- 4. Low noise
- 5. Good overload margin

The V90-LPS has extremely accurate RIAA correction and that extends up to 80 kHz and beyond. That may sound extreme, but there is a good deal of information above 20 kHz that needs correction. If it isn't corrected, it will show itself as ringing and overshoot. The V90-LPS's distortion is very low. Noise ratio is extremely low and all but inaudible.

Overload margin is easily adequate for any current cartridge.

All in all, the V90-LPS accomplishes everything necessary for a phono stage.

There are many phono stages that are far more expensive and make extraordinary claims for their performance. In contrast, the modest V90-LPS just gets on with the job of doing everything you could reasonably expect from a phono stage.

If you want top notch performance, and don't care about the alleged conferred status of buying a highpriced product that offers no better performance than the V90-LPS, then we are of a like mind.

V90-LPS In Brief

- Switchable MM / MC input
- Extremely accurate RIAA extending out to at least 60kHz
- Very low noise (virtually inaudible)
- Very low distortion
- Excellent overload margin
- Excellent channel separation
- Beautiful, considered build quality

MUSICAL FIDELITY



V90-LPS PHONO STAGE

SPECIFICATION

Performance

Input impedance: 47kOhm (MM), 100Ohm (MC) Input sensitivity: 3.0mV (MM), 400µV (MC) for 300mV out

Total harmonic distortion: 0.01% (MM/MC) -@ 1kHz, 300mV out

Frequency Response: +0, -0.1dB, 20Hz to 20 kHz Signal / Noise ratio (A weighted): >80dB (MM), >70dB (MC)

Input overload margin: 15dB (MM), 22dB (MC) RIAA response: +/- 0.25dB

Inputs

MM: 1 pair RCA sockets MC: 1 pair RCA sockets Outputs

1 pair RCA sockets

General

Dimensions - WxHxD (mm): 170 x 47 x 102 Weight (unpacked / packed): 600g / 1.1 kg

Supplied Accessories 1x 12v 500mA DC power supply